



CB6118-12 Reloading Data ~ 1 1/8 Ounce Shot Loads

All Straight Wall Hulls Including Imports

----- Plastic hull Data -----

Primer	Powder	Grains	Velocity F.P.S.	Pressure P.S.I
Fed 209A	American Select	18.5	1090	5330
Fed 209A	American Select	20	1145	6110
Fed 209A	American Select	20.5	1200	6740
Fed 209A	Clay Dot	16.5	1090	6710
Fed 209A	Clay Dot	18	1145	7870
Fed 209A	Clay Dot	19	1200	9540
Fed 209A	e3	15	1090	7070
Fed 209A	e3	16.5	1145	8100
Fed 209A	e3	17.5	1200	8940
Fed 209A	Green Dot	18	1090	6900
Fed 209A	Green Dot	19.5	1145	7220
Fed 209A	Green Dot	20.5	1200	7800
Fed 209A	Red Dot	16.5	1090	7290
Fed 209A	Red Dot	17.5	1145	8140
Fed 209A	Red Dot	18.5	1200	8690

----- Paper hull Data -----

Primer	Powder	Grains	Velocity F.P.S.	Pressure P.S.I
Fed 209A	American Select	19.5	1145	7290
Fed 209A	American Select	20.5	1200	8130
Fed 209A	American Select	22	1250	9440
Fed 209A	Clay Dot	18	1145	7390
Fed 209A	Clay Dot	19	1200	8690
Fed 209A	Clay Dot	20.5	1250	10390
Fed 209A	e3	17	1145	8500
Fed 209A	e3	18	1200	9200
Fed 209A	e3	19	1250	10410
Fed 209A	Green Dot	20	1145	7380
Fed 209A	Green Dot	21	1200	7810
Fed 209A	Green Dot	22.5	1250	8840
Fed 209A	Red Dot	18	1145	8550
Fed 209A	Red Dot	19	1200	9160
Fed 209A	Red Dot	20	1250	9910